



## KENWORTH PRIMEMOVER



### SPECIFICATIONS

Model	T409SAR	Rr Axle Load (kg)	16500
Type	Prime Mover	Max Rear Load (kg)	16500
Description	New Pres 101833	Distance at Max Rear Load (%)	100
Intended Serv.	Processed Quarry Products	G.C.M. (kg)	42500
Commodity	Gravel/Crushed Rock/Sand	Max G.C.M. Load (kg)	42500
<b>Trailer</b>		Distance at Max G.C.M. Load (%)	100
Type:	Side Tipper	Wheelbase (mm)	4830
Length (mm)	15000	Fr Axle to BOC (mm)	2,095
<b>Height (mm)</b>	4300	Cab to Axle	2,735
Kingpin Inset (mm)	1430	Cab to EOF	4,105
Corner Radius (mm)	0	Road Conditions	
Trailer Width (mm)	2500	Class A (I'state hwy/Roads)	100
<b>Restrictions</b>		Class B (Well Maintained)	0
Length (mm)	19000	Class C (Poorly Maintained)	0
Width (mm)	2500	Class D (Off-Road)	0
Height (mm)	4300	Maximum Grade	8
<b>Chassis</b>		Length Max Grade (km)	0
Fr Axle Load (kg)	6000	Normal Grade (%)	0
Max Front Load (kg)	6000	Length Normal Grade (km)	0
Distance at Max Load (%)	100	Annual Distance (km)	250000

### CIVIL & MARINE INFRASTRUCTURE SPECIALISTS