

CivilPlus CONSTRUCTIONS

BOBCAT S185 SKID STEED LOADER



SPECIFICATIONS

Length with Bucket	10.9ft in	3310mm	Operating Speed	7.3mph	11.7km/h
Width Over Tires	5.5ft in	1676mm	Loader		
Height to Top of Cab	6.4ft in	1938mm	Operating Load Rating	1850lb	839.1kg
Wheelbase	3.4ft in	1030mm	Tipping Load	4076lb	1848.8kg
Ground Clearance	7.5in	190mm	Bucket Capacity	0.43yd3	0.33m3
Length W/O Bucket	8.5ft in	2588mm	Hydraulic		
Clearance at Max Lift and Dump	7.6ft in	2310mm	Pump Flow Capacity	16.9gal/min	64L/min
Reach at Max Lift and Dump	29.6in	753mm	Relief Valve Pressure	330psi	22752.7kPa
Engine			Dimensions	•	
Make	Kubota		Length with Bucket	10.9ft in	3310mm
Model	V2003-M-DI-T		Length W/O Bucket	8.5ft in	2588mm
Gross Power	56hp	41.8kw	Width Over Tires	5.5ft in	1676mm
Power Measured @	2800rpm		Height to Top of Cab	6.4ft in	1938mm
Displacement	122cu in	2L	Clearance at Max Lift and Dump	7.6ft in	2310mm
Number of Cylinders	4		Wheelbase	3.4ft in	1030mm
Operational			Ground Clearance	7.5in	190mm
Operational Weight	6220lb	2821.3kg	Reach at Max Lift and Dump	29.6in	753mm
Fuel Capacity	24gal	91L	Turning Radius from Centre – Machine Rear	78.8in	2001.5mm

CIVIL & MARINE INFRASTRUCTURE SPECIALISTS