ABN: 26 010 438 703



CATERPILLAR HYDRAULIC EXCAVATOR 305c



SPECIFICATIONS

| Shipping Length of Unit | 17.5ft in | 5330mm | Net Power | 47hp | 35kw |
|---------------------------------|------------|--------|---|-------------|----------|
| Shipping Height of Unit | 8.3ft in | 2550mm | Power Measured @ | 2400rpm | |
| Max Cutting Height | 17.6ft in | 5370mm | Displacement | 153cu in | 2.5L |
| Max Loading Height | 12.5ft in | 3800mm | Number of Cylinders | 4 | |
| Max Reach Along Ground | 18.6ft in | 5650mm | Operational | | |
| Max Vertical Wall Digging Depth | 8.3ft in | 2530mm | Operating Weight | 11725lb | 5230kg |
| Max Digging Depth | 11.4ft in | 3490mm | Fuel Capacity | 19gal | 72L |
| Dimensions | | | Cooling System | 2.9gal | 11L |
| Width to Outside of Tracks | 6.5ft in | 1980mm | Hydraulic System Fluid Capacity | 0.6gal | 78L |
| Length of Track on Ground | 8.5ft in | 2580mm | Engine Oil Capacity | 1.9gal | 7L |
| Ground Clearance | 1.1ft in | 340mm | Operating Voltage | 12V | |
| Height to Top of Cab | 8.3ft in | 2550mm | Alternative Supplied Amperage | 50amps | |
| Tail Swing Radius | 3.2ft in | 990mm | Hydraulic System Relief Valve Pressure | 3553psi | 24500kPa |
| Counterweight Clearance | 2ft in | 615mm | Hydraulic Pump Flow Capacity | 34.3gal/min | 130L/min |
| Undercarriage | | | Swing Mechanism | | |
| Track Gauge | 5.2ft in | 1580m | Swing Speed | 9rpm | |
| Shoe Size | 16in | 400mm | Undercarriage | | |
| Engine | | | Shoe Size | 16in | 400mm |
| Make | Mitsubishi | | Max Travel Speed | 2.8mph | 4.6km/h |
| Model | S4Q2-T | | Track Gauge | 5.2ft in | 1580mm |
| Gross Power | 49.2hp | 36.7kw | | | |

CIVIL & MARINE INFRASTRUCTURE SPECIALISTS

www.civilplus.com.au

PH: 07 4727 0200