

CivilPlus CONSTRUCTIONS

CATERPILLAR 330 3D EXCAVATOR



SPECIFCATIONS

| | | Cooling System Fluid Capacity | 6.6gal | 25L |
|-------------|---|---|---|---|
| 9.8ft in | 2940mm | Hydraulic System Fluid Capacity | 81.9gal | 310L |
| 15.11ft in | 4860mm | Engine Oil Capacity | 6.6gal | 25L |
| 17ft in | 490mm | Swing Drive Fluid Capacity | 2.6gal | 10L |
| 10.0ft in | 3060mm | | | |
| 10.3ft in | 3130mm | | | |
| 3.8ft in | 1120mm | Swing Mechanism | | |
| | | Swing Speed | 11.50rpm | |
| Caterpillar | | Swing Torque | 63,652lb ft | 86 kNm |
| 330 3D | | Undercarriage | | |
| 273hp | 204kw | Shoe Size | 24in | 600mm |
| 428cu in | 7.01L | Max Travel Speed | 3.3mph | 5.3km/h |
| | | Drawbar Pull | 55,753lbf | 248kN |
| 66,000lb | 30,000kg | Track Gauge | 8.6ft in | 2590mm |
| 125.2gal | 474L | | | |
| | 15.11ft in 17ft in 10.0ft in 10.3ft in 3.8ft in Caterpillar 330 3D 273hp 428cu in | 15.11ft in 4860mm 17ft in 490mm 10.0ft in 3060mm 10.3ft in 3130mm 3.8ft in 1120mm Caterpillar 330 3D 273hp 204kw 428cu in 7.01L 66,000lb 30,000kg | 9.8ft in 2940mm Hydraulic System Fluid Capacity 15.11ft in 4860mm Engine Oil Capacity 17ft in 490mm Swing Drive Fluid Capacity 10.0ft in 3060mm 10.3ft in 3130mm 3.8ft in 1120mm Swing Mechanism Swing Speed Caterpillar Swing Torque 330 3D Undercarriage 273hp 204kw Shoe Size 428cu in 7.01L Max Travel Speed Drawbar Pull 66,000lb 30,000kg Track Gauge | 9.8ft in 2940mm Hydraulic System Fluid Capacity 81.9gal 15.11ft in 4860mm Engine Oil Capacity 6.6gal 17ft in 490mm Swing Drive Fluid Capacity 2.6gal 10.0ft in 3060mm 3130mm 3.8ft in 1120mm Swing Mechanism Swing Speed 11.50rpm Caterpillar Swing Torque 63,652lb ft 330 3D Undercarriage 273hp 204kw Shoe Size 24in 428cu in 7.01L Max Travel Speed 3.3mph Drawbar Pull 55,753lbf 66,000lb 30,000kg Track Gauge 8.6ft in |

CIVIL & MARINE INFRASTRUCTURE SPECIALISTS